

The background features a soft-focus image of green leaves and two butterflies. One butterfly is purple and green, and the other is blue and brown. The text is overlaid on a light blue curved graphic.

Physical Pharmacy / Lab - 4 -

Surface Tension

WHAT IS SURFACE TENSION?

- Surface Tension is defined as the tension of the surface film of a liquid caused by the attraction of the particles in the surface layer by the bulk of the liquid, which tends to minimize surface area.
- It is due to the phenomena of surface tension that the drops of water tend to assume a spherical shape to attain minimum surface area.



Examples of Surface Tension



Walking on water:

Small insects such as the water strider can walk on water because their weight is not enough to penetrate the surface.




Floating a needle: A carefully placed small needle can be made to float on the surface of water even though it is several times as dense as water. If the surface is agitated to break up the surface tension, then needle will quickly sink.



Surface Tension and Droplets:


Surface tension is responsible for the shape of liquid droplets. Although easily deformed, droplets of water tend to be pulled into a spherical shape by the cohesive forces of the surface layer.

- **surface** is used when referring to either a gas-solid or a gas-liquid interface.
- **The tension in the surface:** is the force per unit length that must be applied to the surface so as to counterbalance the net inward pull. It has the units of dyne/cm. as shown in Figure 1.





- **Interfacial tension:** is the force per unit length existing at the interface between two immiscible liquid phases and has the unit of dynes/cm.
- ordinarily; it is less than surface tension because the adhesive forces between liquid phases forming an interface are greater than when a liquid and a gas phase exist together.
- It follows that if two liquids are completely miscible; no interfacial tension exists between them.



Furthermore, there are two important terms related to forces.





First, Cohesive forces are the intermolecular forces which cause a tendency in liquids to resist separation. These attractive forces exist between molecules of the same substance.
,While

Second, adhesive forces are the attractive forces between unlike molecules. They are caused by forces acting between two substances, such as mechanical forces (sticking together) and electrostatic forces (attraction due to opposing charges)



Surface tension

- The **cohesive** forces among the liquid molecules are responsible for this phenomenon



Factors affecting surface tension

1. Temperature

2. **Surface active agents(S.A.A)**: addition of surfactants to water decreases the surface tension. Because surfactants in water orient themselves at interface in such away to remove hydrophobic tail away from aqueous phase, as a result some of water molecules at the interface replaced by non-polar part of surfactant and since attractive force between surfactant molecules (cohesive force) & between S.A.A and water (adhesive force) less than cohesive force between water molecules a lone (i.e. decrease cohesive force leads to decrease net effect (cohesive- adhesive) leads to decrease surface tension).



Methods to measure surface tension

There are several methods of surface tension measurements:

1. Drop weight method: The surface tension of the liquid is related to the weight of a drop of that liquid which falls freely from the end of the tube by the expression

$$\gamma = \frac{MG * F}{R}$$

γ = surface tension (gm.cm/sec² = dyne /cm)

M=mass of one drop,

R= radius,

F= correction factor

G= 980 cm/sec² or 9.8 m/sec²



Procedure

1- Check that the glass tip is very clean & free from any defect particularly around the edges

2-Allow the drop (e.g. water) to detach slowly from the tip & collect 10 -15 drops in a beaker under constant conditions (constant temperature).

3-Finally, measure the radius of tip.

It is important that the drop has been correctly formed & detached and the rate of detachment should not exceed 1 drop in 2 sec, & vibration must be guarded against as well as check the end of the tip is horizontal.



2. Modification of drop weight method (drop number method):-

It may be performed by counting the numbers of drop (n) by certain volume (0.5 ml) under conditions similar to that prescribed previously. A comparison with liquid of known surface tension must be similarly treated by using the same tube under the same condition.

$$\frac{\gamma_1(\text{water})}{\gamma_2(\text{tween})} = \frac{m_1}{m_2} \quad (m = \text{density} * \text{volume}).$$

$$\frac{\gamma_1}{\gamma_2} = \frac{d_1^3 (0.5/n_1)}{d_2^3 (0.5/n_2)}$$

$$\frac{\gamma_1}{\gamma_2} = \frac{d_1^3 n_2}{d_2^3 n_1}$$

Surface tension of water =72.8 at 25 c° & d=1



3. Ring detachment method (Du Noüy Ring

Tensiometer): The principle of the instrument depend on the fact that the force necessary to detach a platinum ring immersed at the surface or interface is proportional to the surface or interfacial tension.



4- Capillary rise method:-

In this method when inverted tube (capillary tube) in a liquid, the tube will be risen up to a certain distance by a liquid , it depends on:

- surface tension of liquid (increasing surface tension leading to increase height of liquid) and
- on the cross section area of that tube (increase area leads to increase height)for the cross section area at any point upward force resulting from the surface tension of the liquid on the circumference.



Experimental work

The aim of the experiment is to determine the surface tension of liquids in addition to the C.M.C. of surfactant such as tween.

Materials and equipment:-

- Distilled water, alcohol, solution 2% tween60
- graduated pipette, weighing bottles , beaker , conical and volumetric flask(50 cc).



Procedure:

1. Use modified drop method to measure the surface tension of the concentrations of tween60 (0.01%, 0.03 %, 0.05%, 0.075%, 0.1%, 0.2%), then prepare 50 ml of each solution by dilution method using 2% stock solution.
2. Plot surface tension versus concentration.
3. Determine C.M.C. of tween60 from the plot ($n_{\text{water}}=16$) ($\delta_{\text{water}} = 72.8$).

The densities of the concentration used are as follows:-

<i>density</i>	<i>Concentration</i>
<i>1.01</i>	<i>0.01</i>
<i>1.02</i>	<i>0.03</i>
<i>1.04</i>	<i>0.05</i>
<i>1.05</i>	<i>0.075</i>
<i>1.1</i>	<i>0.1</i>
<i>1.2</i>	<i>0.2</i>

Use water as a standard liquid (surface tension =72.8 & its density = 1).



*Thank You For
Listening*

It's time for question???

